



NATIONAL AUTO SPORT ASSOCIATION

RACE CAR ANNUAL INSPECTOR'S FORM

THIS FORM IS TO BE COMPLETED BY AUTHORIZED NASA TECH PERSONEL
DRIVERS SHALL MAINTAIN THIS COMPLETED FORM WITH THE LOGBOOK FOR THE DURURATION OF
THE RACING SEASON

Version 2.0

Driver/Owner Name. First: _____ Last: _____

Make: _____ Model: _____ Class: _____ Color: _____ Number: _____

VEHICLE EXTERIOR

- Windshield clips
- Tow hooks F/R
- Muffler exit

ROLL CAGE

- Cage # Stamped _____
- Main Hoop 1 piece, 4 bends
- Rear down tubes not bent
- Door Bars: 2 driver, 1 passenger
- Mounting plates, Plinth boxes
- 360 welds on required boxes
- 3 x 3/16" inspection holes
- Padding on contact areas

ENGINE COMPARTMENT

- Coolant overflow tank
- No antifreeze in coolant system
- No fluid leaks, oil or coolant
- Condition of hoses
- Battery secure, + terminal covered
- No firewall holes
- Brake fluid level
- No exposed wiring

DRIVER COMPARTMENT

- Master switch function test
- Master switch terminals covered
- Master switch decal installed
- Ballast mounting and plates
- Extinguisher within drivers reach
- Extinguisher 2lbs minimum as per CCR 15.1
- Metal extinguisher mounting plate/brackets
- Fluid hoses or steel Braided Line

DRIVERS SEAT

- Back brace for non-FIA or expired seat. (5 years)
- Back brace load spread
- Seat bolted in tight - mounting _____
- Right side drivers net or seat bolster

HARNES

- SFI 16.1/5 & <2 years old.
- Note manufacture date _____
- Current FIA belts
- Note manufacture date _____
- Mounting points
- Backing plates
- Condition of webbing
- Shoulder belt mounting no more than 20 degrees from horizontal
- Lap belt mounting
- Submarine belt mounting
- Harness threaded 3 times
- Safety clips installed

WINDOW NET

- Less than 5 years old
- Release from top front
- Mounting points on cage
- Condition of webbing

FIRE SYSTEM

- Control within drivers reach
- 5lb min full (see 15.2 in the CCR)
- Minimum of 1 nozzle in driver's compartment
- Minimum of 1 nozzle in engine compartment
- Mounting brackets/plates bolted in securely
- Extinguisher decal installed accurately for location

FUEL TANK / CELL

- Cell manufacturer date in logbook
- Bladder <5 years old
- Cell flapper valve
- Cell condition and mounting
- Gas cap secured

DRIVER GEAR AND EQUIPMENT

- Head and neck restraint system rated SFI 38.1 & <5 years old, or FIA 8858-2002/2010 or newer
- Driver suit rated SFI 3.2/A1 or 3.4/5 or FIA 8856-2000
- Helmet rated: SA2010, 31.1/2005. FIA 9900-2010 or newer
- Shoes rated SFI/FIA or leather with no holes
- Gloves rated SFI/FIA with no holes excessive wear
- Fire resistant underwear, if required
- Fire resistant socks
- Fire resistant balaclava

Season Annual Valid for: _____ Inspectors Name _____ Log book # _____

Signature or Shop Stamp: _____ Date: _____ SFI # _____

Note: Vehicles may meet other recognized sanctioning body's safety rules, providing the vehicle is 100% compliant with those rules, per CCR 15.24. Mixing and matching safety rules between sanctioning bodies is prohibited, unless specifically permitted in writing from the National Office.