



SpecZ

2018 EDITION

THIS BOOK IS AN OFFICIAL PUBLICATION OF THE
NATIONAL AUTO SPORT ASSOCIATION. COPYRIGHT ©2018
ALL RIGHTS RESERVED

THE CONTENTS OF THIS BOOK ARE THE SOLE PROPERTY OF THE NATIONAL AUTO SPORT ASSOCIATION. NO PORTION OF THIS BOOK MAY BE REPRODUCED IN ANY MANNER, ELECTRONICALLY TRANSMITTED, POSTED ON THE INTERNET, RECORDED BY ANY MEANS, OR STORED ON ANY MAGNETIC / ELECTROMAGNETIC STORAGE SYSTEM(S) WITHOUT THE EXPRESS WRITTEN CONSENT FROM THE NATIONAL EXECUTIVE DIRECTOR OF THE NATIONAL AUTO SPORT ASSOCIATION.

National Auto Sport Association, Inc.
National Office
P.O. Box 21555
Richmond, CA 94820
<http://www.nasaproracing.com>
510-232-NASA
510-412-0549 FAX

SpecZ

Copyright 2018, National Auto Sport Association

Official Rules

Rules Subject To Change

1. Introduction

The NASA Spec Z class is an affordable racing series, primarily focused on road racing, and shall function as an advertising and marketing tool for the series sponsors, the independent sponsors of each team, as well as the official sanctioning body of the series. The trade name, "NASA Spec Z," and these rules are the property of the National Auto Sport Association, Incorporated ® located at P.O. Box 2366 Napa Valley, CA 94558; 510-232-NASA (6272).

2. Intent

The intent of these rules is to provide mandates to ensure that all vehicles are constructed and modified within clearly established limits, so as to ensure an even platform, in which a contest of driving skill may provide the most talented drivers with great rewards.

3. Sanctioning Body

SpecZ is supported and sanctioned by the National Auto Sport Association (NASA). All race events are governed by the rules set forth by the Class/Series Directors and NASA officials. All competitors agree to also abide by the rules set forth in NASA's current Club Codes and Regulations (NASA CCR) and any supplemental rules issued by the Class/Series Directors.

4. Vehicle Specifications

4.1 Eligible Manufacturers

Nissan Motor Corporation is the only manufacturer of models that are legal for this series. However, other companies, including NISMO, which should be considered a separate company from Nissan Motor Corporation, may manufacture some legal and/ or required parts and components.

4.2 Eligible Models/Weight/HP

Any Model Nissan 350Z is eligible for competition in the Spec Z series. Any model 350Z may compete as delivered from the factory, given all CCR safety requirements are met. Additional components that were provided on the factory Nismo version of the 350Z may be added to any other model of 350Z excluding engine components. This includes brake components and exterior body panels.

Year	Make	Model	Motor	Note	Weight (lb)
03-04	Nissan	350Z	VQ35DE	Engine must be intake only variable timing controlled	3100
05-06	Nissan	350Z	VQ35DE	Engine must be intake and exhaust variable timing controlled	3175
07-08	Nissan	350Z	VQ35HR	Any dual Throttle Body engine'd car must run as 07-08	3325

4.3 Horsepower Limits

- 4.3.1 NASA will impose a maximum horse power limit for each Spec-Z engine classification.
- 4.3.2 Horsepower readings will be measured utilizing a Dynojet Dynamometer with the SAE correction factor and smoothing factor of "5".
- 4.3.3 NASA may impound all competitors and require certain competitors to report to the dyno located trackside for Dynojet Dynamometer testing immediately following any on track session.
- 4.3.4 Any competitor found to be competing over the allowed maximum horse power limit for their particular engine classification will be disqualified from their previous session unless they are found to have an additional 20lbs for each horse power they are over the maximum limit for the duration of the event.
- 4.3.5 NASA may also utilize data acquisition systems to measure real time acceleration rates during competition to supplement the trackside dynamometer testing.

Spec-Z competitors should refer to the table below to find their specific maximum horsepower limit for both regional and championship events.

Year	Make	Model	Motor	Note	Horsepower
03-04	Nissan	350Z	VQ35DE		258
05-06	Nissan	350Z	VQ35DE		265
07-08	Nissan	350Z	VQ35HR		275

5. Safety

- 5.1 Gusseting of the a-pillar to the front hoop of the roll cage is allowed.

6. Modifications

6.1 Engine

6.1.1 General

- 6.1.1.1 All engines, components, and parts must have been offered for sale in a Nissan 350Z, sold by a dealer in the United States of America unless otherwise specified in these rules.
- 6.1.1.2 For all Nissan part numbers in these specifications, superseding part numbers are considered equivalent.
- 6.1.1.3 No modifications to the engine are allowed, except provided by these rules. All engines and their internal components must remain stock Nissan OEM and within factory specified tolerances. No balancing, over-boring, blue printing, lightening, polishing, or other modification of moving parts of the engine is permitted.
- 6.1.1.4 Cast iron cylinder liners (sleeves) may be installed to restore damaged or worn cylinder bores to the original dimension.
- 6.1.1.5 Balancing of Flywheel is permitted, but material may only be removed for the purpose of balancing that item.
- 6.1.1.6 DE Engines may omit the upper idler pulley and belt with a shorter belt, OEM part number 11720-4P10A or equivalent.
- 6.1.1.7 Maximum allowed compression ratios are shown in the following table:

Model Years	Compression Ratio
03-06	10.3:1
07-09	10.6:1

6.1.2 Cylinder Head

- 6.1.2.1 The cylinder head must not be modified, ported, polished, or machined unless specified within these rules.
- 6.1.2.2 Valve face where it mates to the seat and valve seats may be machined for the purposes of a valve job.
- 6.1.2.3 Valves and stem seals may only be replaced with OEM Nissan parts. Valve location or angle must not be moved. Reshaping of the valves is strictly prohibited. Valve guides may be replaced provided the position of the valve is not changed and the replacement guides are Nissan OEM parts. Valve stem installed height must be per the Nissan factory specifications.
- 6.1.2.4 Camshafts must be OEM for year of engine being used and shall not be replaced or modified outside of stock specifications. Cams ground from blanks or reground cams are not acceptable. No mixing of cams between engine models.

6.1.3 Cooling System

- 6.1.3.1 Oil cooler, oil filter, remote filter mount, lines and adapters are free. OEM components are also legal.

- 6.1.3.2 Any radiator may be used, provided that it mounts in the stock location, without any modification of any part of the stock mounting location that is integral to the body. Any additional open areas or holes created by use of a non-OEM radiator may be blocked off, but under no circumstance shall the open areas or holes be used for supplying the air filter with additional air.
- 6.1.3.3 Thermostats are optional and unrestricted, providing that they serve no other function than to control coolant flow from the engine to the radiator.
- 6.1.3.4 Heater core may be bypassed or removed. The rubber hoses that supply water to the heater core may be shortened or eliminated.

6.2 ECU/Induction/Exhaust/Fuel Systems

- 6.2.1 All vehicles must use unmodified stock air filter housing. Air filter element is unrestricted, but must be utilized.
Note: A restrictor plate may be specified for any engine type for the purpose of maintaining class parity. In the event a restrictor plate is mandated or the size of an already mandated restrictor plate is changed, a grace period of 30 days will be given before the new plate or sized plate must be complied with
- 6.2.2 Any spark plug may be used
- 6.2.3 Initial ignition timing may be set by ECU only.
- 6.2.4 Battery size and type is unrestricted, but must be securely mounted in the stock location and must be capable of starting the car. Relocation of battery outside of factory battery compartment is not permitted.
- 6.2.5 Factory ECU must be retained. "Reflashing" of factory ECU is permitted. Replacement or "piggy back" systems are not permitted.
- 6.2.6 Replacement of OEM exhaust system downstream from factory exhaust manifold is permitted and unrestricted providing it exits aft of the rear sub-frame. NISMO Cat-back system is also permitted. Exhaust manifolds must match the year range of the engine installed.
- 6.2.7 Stock exhaust heat shielding may be removed.
- 6.2.8 Fuel usage is restricted to unleaded gasoline commonly found at track side retail pumping. Octane is limited to a maximum of $100 (R+M)/2$ as labeled on the pump. Race fuels such as, but not limited to, ERC brand are prohibited. All fuel additives are illegal, per the CCR. Note-event supplemental rules supersede this section.
- 6.2.9 The EVAP system may be disabled or completely removed.
- 6.2.10 Any submersible fuel pump and fuel line may be added to the left side of the tank for the sole purpose of transferring fuel from the left side of the fuel tank to the right side of the fuel tank to prevent fuel pump starvation. This pump must not in any way pressurize the existing fuel system. The installation must be professional, be fully sealed, and have no exposed wiring.
- 6.2.11 Fuel filler trap door and restrictor plate in the filler neck may be removed.

6.2.12 Fuel injectors, rails, feed/return lines, regulator, and dampener must remain OEM and unmodified.

6.3 Transmission/Clutch & Flywheel/Differential

6.3.1 See Appendix A for permitted Clutch, NISMO Flywheel, NISMO or Wavetrac Limited Slip Differentials, and NISMO Differential Cover.

6.3.2 Transmission must be unmodified except for the Clutch Arm Pivot Ball which may be replaced with any ferrous material in the same shape and size as OEM.

6.3.3 Pressure plate and clutch disk are unrestricted provided the unit is a single disc clutch system weighing no less than 13.5lbs for the pressure plate, and 3.5lbs for the clutch disc.

6.3.4 OEM final drive must be retained.

6.3.5 Differential cooler may be added and utilized. Size and location is unrestricted.

6.3.6 The stock rubber differential bushings may be replaced with any non-metallic bushings. No bushing may alter original suspension geometry.

6.4 Suspension Components

6.4.1 Suspension

6.4.1.1 See Appendix A for permitted shocks, springs, NISMO sway bars, and NISMO bushings.

6.4.1.2 Ride height is unrestricted providing that no metal part of the vehicle touches the ground so as to be hazardous in the opinion of the Race Director.

6.4.1.3 Front upper control arms (A-Arms) may be replaced with aftermarket components for the purpose of adjusting front wheel camber. Factory mounting positions must be retained.

6.4.1.4 Rear camber is unrestricted provided it is within the limits of adjustment using the stock OEM arms only.

6.4.1.5 A single 2 (two) inch circular hole may be cut in the rear strut tower brace directly above the rear shock for the single purpose of accessing the rear shock rebound adjuster.

6.4.1.6 A single 20mm diameter hole may be cut in the front strut tower brace for the single purpose of making the install of the spec coil over kit easier.

6.5 Steering

6.5.1 Optional OEM Power Steering Cooling system may be added to any vehicle not originally equipped. Larger NISMO power steering cooler may be used in place of OEM cooler.

6.6 Wheels and Tires

6.6.1 Any eighteen (18.00) inch diameter rim, with a maximum width of ten (10.00) inches may be used on the front or rear axle positions.

6.6.2 No wheel permitted for competition use can weigh less than eighteen point five (18.50) pounds with the exception of the Enkei RPF1 being specifically permitted for competition use.

6.6.3 Wheels must be one piece. (i.e. No multi piece bolted, riveted, or welded wheels).

- 6.6.4 Aftermarket wheel studs, lug nuts, and wheel spacers are permitted. Refer to Appendix A for recommended Nissan Part(s).
- 6.6.5 Toyo RR, size 275/35/ZR18, is the spec tire for dry weather use. Toyo RA1, size 275/35/ZR18, is allowed for wet weather use.

6.7 Brake System

- 6.7.1 Brake pads are unrestricted.
- 6.7.2 Brake rotors must be the same type, material, and dimensions as OEM. Brake rotors from alternate companies may be used. Brake rotors may be cryogenically treated.
- 6.7.3 Steel braided brake lines may be used.
- 6.7.4 Disc brake backing plates may be removed.
- 6.7.5 The emergency brake level and/or cables and associated must remain functional.
- 6.7.6 Anti-lock braking systems (ABS) may be disabled.
- 6.7.7 Manual brake bias valve is permitted only in the event that ABS system is disabled.
- 6.7.8 Two holes, no larger than 3.5"x5.75" or 5.25" in diameter may be cut in the front bumper cover for the sole purpose of routing cooling air to the front braking system.
- 6.7.9 Alternate brake package from the 350Z/Akebono 370Z Sport brakes are allowed but must be used in their entirety front and rear.

6.8 Appearance

6.8.1 Exterior

- 6.8.1.1 See Appendix A for permitted NISMO exterior body components.
- 6.8.1.2 Nissan Contingency Decals following the Nissan Contingency Guidelines are required on each Spec-Z competing at any regional or national event.
- 6.8.1.3 Fenders and wheel openings must remain unmodified, except that rolling or flattening of inner fender lip for tire clearance is permitted.
- 6.8.1.4 Hood and inner fender plastic trim are optional and may be removed.
- 6.8.1.5 Louvered style hood vents not exceeding a total of 400 square inches in total area are permitted. Inner hood structure may be removed only in areas that facilitate installation of the vent and mounting hardware.
- 6.8.1.6 Any mirrors may be used or removed.
- 6.8.1.7 Any paint scheme / colors may be applied.
- 6.8.1.8 Front/Rear wipers with motors and hardware, license plates with frames and lights, body molding, horns, antenna, and air bag sensors/wiring may be removed.
- 6.8.1.9 Windshield clips and rear window straps are permitted.
- 6.8.1.10 Hood clips are permitted. Stock hood latches may be disabled or removed.

6.8.2 Interior

- 6.8.2.1 The transmission tunnel may be modified for the purpose of installing a competition driver seat. The floor pan must remain in its original position
- 6.8.2.2 Gauges may be added, replaced, or removed.
- 6.8.2.3 Any steering wheel and attachments may be used except wood rimmed type steering wheels.
- 6.8.2.4 Any shift knob may be used.
- 6.8.2.5 Other than modifications made to mount instruments and provide for roll cage installation, the remainder of the dash board and instrument panel must remain intact.
- 6.8.2.6 The air conditioning system, carpet, all insulation material, center console, cargo bins, OEM seat belts, air bags, radio system, headliner, dome lights, grab handles, spare tire, tools, removable interior panels, and passenger seat may be removed.
- 6.8.2.7 Rear speaker Main Box 74552-CD000, center support bracket 74554-CD000, center support connecting bracket 74554-CD010, side brackets 766A6-CD000 and 766A7-CD000 may be removed.
- 6.8.2.8 Removal or substitution of driver compartment panels is not permitted.
- 6.8.2.9 Ducting may be added to provide fresh air to the driver/passenger compartment, providing that no modifications of windows and body structure are made to accommodate this addition.
- 6.8.2.10 The foot pedals (i.e. brake, clutch, gas) may be modified for driver comfort and accessibility. Additionally, modifications for strengthening are allowed provided that those modifications serve no other purpose.
- 6.8.2.11 The door window glass, window operating mechanism, and inside door latch/lock operating mechanism may be removed and the inner door structural panel may be modified, but not removed. The outside door latch/lock operating mechanism shall not be removed or modified. The stock side impact beam may be removed or modified, this gutting of the door shall only be made if roll cage incorporates NASCAR style side protection extending into the door.
- 6.8.2.12 Other than to provide for the installation of required safety equipment or other authorized modifications, no other driver/passenger compartment alterations or gutting is permitted.

7. Class Directors, Social Media

Facebook group: NASA SpecZ

Tom Kaminski –SpecZ national director

Email: Tom.W.Kaminski@gmail.com

Call or Text: (512) 799-5139

Rich Fitzgerald – Co-SpecZ national director
 Email: spec350zracer@yahoo.com
 Call or Text: (801) 310-5118

8. Appendix A. Recommended Nissan Performance Parts for the preparation of a NASA Spec Z competition vehicle.

For both OEM and NISMO parts ordering, contact Nissan Motorsports at nmc.race@nissan-usa.com or 888-833-3225.

Part	Detail	Note	Motorsports part
ECM			
OEM only	Reflash allowed	Reflash maps available from Nissan Motorsports	
Exhaust			
NISMO Cat back	Free		20100-RSZ35
Cooling			
Radiator	Free	OEM dimensions in height and width	21400-CDZ33
Oil Cooler	Free		21300-RSZ33
Drive train			
OEM Clutch disc	Free single disc	OEM dimension	30100-CD019
OEM Pressure Plate	Free single disc	OEM dimension	32010-CD020
NISMO Flywheel	OEM or NISMO	Only fits 03-06 DE Engine	12310-RSZ30
Differential finned Aluminum cover	OEM final drive	Motorsports rear cover allowed	38351-350DK
Limited Slip Unit	Spec	Wave Trac or NISMO (Must use correct short stub axles and Motul Fluid 101161)	38420-SS370 or 38420-RS141
Short Stub Axle	OEM	LSD equipped cars require 1 additional short stub axle, Non LSD equipped cars require 2	38200-AR011
Wheel			
Wheel stud	Spec	NISMO 60mm (20 needed)	40222-RS045
Lug nut	Spec	Motorsport open end (20 needed)	40222-SS000
Suspension			
Coil over kit	Spec Fr/Rr	KW Double adj	5600S-SZ350
Sway Bar Front	Spec Fr	Progress special for Motorsports	54611-SZ350
Sway Bar Rear	Spec Rr	Progress special for Motorsports	56230-SZ350 (22mm) or 56230-SZ350-19 (19mm)
RF Shock		Replacement Shock	E6110-SZ350
LF Shock		Replacement Shock	E6111-SZ350
Rear Shock		Replacement Shock	E6210-SZ350
Front Spring		Replacement Spring	54010-SZ350

Rear Spring		Replacement Spring	55020-SZ350
Brakes			
Brake lines	Stainless steel		46200-23Z33
Pads	Free	Front	41060-Z33RP
		Rear	44060-Z33RP
Front Brake Duct Kit		Front	99996-Z3350
Body			
All Exterior Body Panels	Must be OEM	All interchange OK	NISMO Z parts
Front Bumper Cover			FBM22-1A45H
Front lip			F2026-1A44A
RH side skirt		Fits on top of OEM side skirt	G6850-1A44H
LH side skirt		Fits on top of OEM side skirt	G6851-1A44H
Rear bumper cover			HEM22-1A45H
Rear cover, lower			H50B2-1A44A
Rear cover, guard			H5050-1A44A
Rear wing upper			K6031-1A44H
Rear wing center			K6074-1A44H
Rear wing lower			K6032-1A44H
Rear wing bracket			K60A0-1A44H
NISMO Hard Rubber Suspension Bushings			
Part No	Description	Needed per car	
54541-RRZ30	Front upper A arm bushing	4	
54560-RRZ30	Front lower transverse link bushing	2	
55045-RRZ30	Rear upper A arm bushing	4	
55148-RRZ30	Rear radius rod (toe link) at hub bushing	2	
55149-RRZ30	Rear radius rod (toe link) at body bushing	2	
55152-RRZ30	Rear lower link (camber link) at hub bushing	2	
55153-RRZ30	Rear lower link (camber link) at body bushing	2	
55158-RRZ30	Rear lower control arm (spring arm) bushing	2	
56218-RRZ30	Rear upper shock absorber bushing	2	